

## P E T I T I O N

Commissioner for Patents  
Alexandria, VA 22313

Your Petitioner, THOMAS A. MOODY, a citizen of the United States and a resident of the State of Washington, whose post office address is 1922 109th Avenue S.E., Bellevue, Washington 98004, prays that Letters Patent may be granted to him for the improvement in a

### METHOD AND MEANS FOR COOLING FUEL OIL CHECK VALVES IN DUAL FUEL GAS TURBINES

as set forth in the following specification.

#### BACKGROUND OF THE INVENTION

##### 1. FIELD OF THE INVENTION

This invention relates to a method and means for cooling fuel oil check valves in dual fuel gas turbines and more particularly to a method and means for cooling the fuel oil check valves in dual fuel gas turbines to prevent the check valves from coking and becoming unreliable and/or inoperable.

##### 2. DESCRIPTION OF THE RELATED ART

In a dual fuel gas turbine, the combustors thereof burn either liquid fuel oil or gaseous fuel in compressed air. The primary reason for a dual fuel gas turbine is that at certain times, the gas fuel price may be extremely high while the price of diesel fuel may be somewhat lower. In those cases, it is desirable to enable the gas turbine to be operated or fueled with liquid fuel such as number two diesel fuel oil. In some dual fuel gas turbines, a check valve is normally imposed in the fuel oil line with that check valve

1 being closed when the turbine is being fueled with gaseous fuel and which is open when  
the gas turbine is fueled with liquid fuel such as number two diesel fuel. When the gas  
turbine is being operated or fueled with gaseous fuel, the oil in the check valve, which is  
in close proximity to the combustor of the gas turbine, is subjected to extremely high  
5 temperatures which sometimes causes the residual oil therein to coke or cake, thereby  
rendering the check valve unreliable or inoperative. This is especially true in the  
General Electric 7FA combustion turbines.

#### SUMMARY OF THE INVENTION

10 A method and means is described for solving the problem of fuel oil check valve  
coking in dual fuel gas turbines. The invention herein is used in combination with a dual  
fuel gas turbine enclosed within an enclosure which is negatively pressurized. One or  
more ambient air inlets are formed in the walls of the enclosure which are in  
communication with a manifold or ambient air conduits which extend from the air inlets  
15 to the fuel oil check valves. The negative pressure within the enclosure causes ambient  
air to be drawn inwardly through the ambient air inlets, through the air conduits and to  
be directed onto the fuel oil check valves to cool the same, thereby preventing coking of  
the check valves when the gas turbine is being fueled by gaseous fuel.

20 It is therefore a principal object of the invention to provide a means for cooling  
the fuel oil check valves in a dual fuel gas turbine to prevent the coking thereof.

A further object of the invention is to provide a method and means for cooling the  
fuel oil check valves of a dual fuel gas turbine which does not require any modification  
of the gas turbine itself.

1 Yet another object of the invention is to provide a method and means for cooling  
the fuel oil check valves of a dual fuel gas turbine through the use of ambient air.

5 Still another object of the invention is to provide a method and means for cooling  
the fuel oil check valves of a dual fuel gas turbine through the use of ambient air and  
which includes means for closing the ambient air inlets by means of a fire dampener  
door.

10 Still another object of the invention is to provide a method and means for cooling  
the fuel oil check valves of a dual fuel gas turbine to increase the reliability of the fuel oil  
check valves.

10 These and other objects will be apparent to those skilled in the art.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 Figure 1 is a partial perspective view of an enclosure which has a dual fuel gas  
turbine positioned therein;

Figure 2 is a partial perspective view of a gas turbine having the ambient air  
cooling means of this invention associated therewith;

Figure 3 is an end view of the structure seen in Figure 2;

Figure 4 is a partial perspective view of an air inlet for the ambient air system;

20 Figure 5 is a perspective view as seen from the inner side of the structure of  
Figure 4;

Figure 6 is a partial sectional view illustrating the manner in which cool ambient  
air is passed over the fuel oil check valve of a combustor; and

Figure 7 is a partial perspective view of illustrating the manner in which the ambient air conduits are connected to the ambient air inlets.

#### DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the drawings, the numeral 10 refers generally to a conventional negatively pressurized enclosure which is positioned upon a slab or other suitable support 12. Enclosure 10 includes opposite end walls 14 and 16 and opposite side walls 18 and 18'. Roof 20 extends over the enclosure in conventional fashion to seal the enclosure. Enclosure 10 includes a pair of access doors 22 and 24. Normally, the enclosure 10 will be negatively pressurized by means of an exhaust fan or blower which exhausts the hot air from within the enclosure 10 in a greater amount than that which enters the interior of the enclosure by way of a conventional air inlet.

The enclosure 10 houses a conventional dual fuel gas turbine which is referred to generally by the reference numeral 26 and which includes a plurality of circumferentially arranged combustors 28 of conventional design. Each of the combustors 28 has a fuel oil line 30 in communication therewith, as viewed in Figure 6. Each of the combustors 28 also has a gas fuel line 32 associated therewith which is connected to a source of gaseous fuel in conventional fashion. The fuel oil line 30 is fluidly connected to a "T" fitting 34, as seen in Figure 6. A fuel oil supply line 36 is connected to the "T" fitting 34, as seen in Figure 6. A fuel oil check valve 38 is imposed in fuel oil supply line 36. The "T" fitting 34 is also connected to a purge air line 40.

When the gas turbine 26 is being fueled with a gaseous fuel through the gas fuel line 32, the check valve 38 is closed so that the combustor 28 is only supplied with the

1 gaseous fuel. When the turbine 26 is being fueled by the gaseous fuel, an extremely  
large amount of heat is generated by the turbine and the temperature adjacent the  
combustor 28 can sometimes reach approximately 300°F, especially those uppermost  
combustors 28. In normal conditions, the check valve 38 is subjected to extreme heat  
5 adjacent the turbine 26 which may cause the fuel oil therein to coke or cake which may  
interfere with the operation of the check valve 38 when the turbine 26 is to be fueled by  
fuel oil such as number two diesel fuel. The combustors 28 at the upper portion of the  
turbine 26 are the combustors which are exposed to the highest temperatures and it is  
the uppermost check valves 38 that tend to coke. Thus, the instant invention has been  
10 provided to prevent the check valves 38 from becoming coked, thereby rendering the  
same unreliable and/or inoperative.

Preferably, side walls 18 and 18' are provided with ambient air inlets 42 and 42',  
respectively. Inasmuch as air inlets 42 and 42' are identical, only air inlet 42 will be  
15 described in detail. Air inlet 42 comprises a plate 44 having a grill 46 supported  
thereon. Preferably plate 44 is secured to the exterior surface of side wall 18 by means  
of screws or the like. A fire dampener door 48 is pivotally or hingedly connected at its  
upper end to the plate 44 at 50 and is movable between open and closed positions with  
respect to the grill 46. An actuator such as a solenoid 52 is operatively connected to the  
20 door 48 for pivotally moving the door 48 between its open and closed positions. Door  
48 is normally open to permit ambient air to be drawn inwardly through the grill 46 due  
to the negative pressure within the enclosure 10. Should a fire occur within the

1 enclosure 10, the actuator 52 will close the door 48 to prevent air from entering the  
enclosure 10 through the grill 46.

5 Box 54 is provided on the interior surface of the plate 44 and has a plurality of  
tubular fittings or pipe stubs 56 extending inwardly therefrom. The inner ends of each of  
the pipe stubs or fittings 56 are operatively connected to an ambient air conduit 58 by  
any convenient means, such as illustrated in Figure 7. The other ends of the ambient  
air conduits 58 have an elbow 60 secured thereto which forms the discharge end of the  
conduit 58. The elbow 60 embraces or surrounds the check valve 38, "T" fitting 34 and  
10 associated structure, as illustrated in Figure 6. Although an ambient air conduit 58  
could be used for each of the combustors 28, it has been found that only the  
combustors 28 at the upper end of the turbine 26 need cooling air and for that reason,  
there is normally no need to supply cooling air to the check valves 38 for each of the  
combustors 28, but the same could be done if so desired.

15 During the operation of the turbine 26 with gaseous fuel, the negative pressure  
within the enclosure 10 will cause ambient air from outside the enclosure 10 to be  
drawn inwardly through the ambient air inlets 42 and 42' and through the air conduits 58  
with the ambient air flowing over the check valves 38, as illustrated in Figure 6, thereby  
cooling the check valves 38 so that the check valves 38 will not coke. The cooler  
20 ambient air drawn into the air conduits 58 ensures that the check valves will remain  
functional.

1           Although a pair of ambient air inlets 42 and 42' are illustrated in Figure 2, it is  
possible that sufficient ambient air may be supplied to the check valves 38 by means of  
a single ambient air inlet which is connected to a plurality of air conduits 58.

5           Thus it can be seen that a novel apparatus and method has been provided for  
cooling the check valves in the fuel oil lines of a dual fuel gas turbine so that the check  
valves will remain functional during the periods that the turbine is being fueled with a  
gaseous fuel and the fuel oil check valves are in the closed position.

10           It can therefore be seen that the invention accomplishes at least all of its stated  
objectives.